


MEMORANDUM

Agenda Item No. 6(P)

TO: Honorable Chairperson Barbara Carey-Shuler, Ed.D. and Members, Board of County Commissioners **DATE:** November 30, 2004

FROM: Robert A. Ginsburg
County Attorney **SUBJECT:** Ordinance relating to
Naranja Community Urban
Center Zoning District

The accompanying ordinance was prepared and placed on the agenda at the request of Commissioner Katy Sorenson.


Robert A. Ginsburg
County Attorney

RAG/bw

Memorandum



Date: November 30, 2004

To: Honorable Chairperson Barbara Carey-Shuler, Ed. D.
and Members Board of County Commissioners

From: George M. Burgess
County Manager

A handwritten signature in black ink, appearing to read "G. Burgess", written over the printed name "George M. Burgess".

Subject: Ordinance relating to Naranja Community Urban Center Zoning District

This ordinance relating to the Naranja Community Urban Center Zoning District will have no fiscal impact on the County.

Fiscal00605



MEMORANDUM

(Revised)

TO: Hon. Chairperson Barbara Carey-Shuler, Ed.D.
and Members, Board of County Commissioners

DATE: November 30, 2004

FROM: Robert A. Ginsburg
County Attorney

SUBJECT: Agenda Item No. 6(P)

Please note any items checked.

- ☐ "4-Day Rule" ("3-Day Rule" for committees) applicable if raised
- ☐ 6 weeks required between first reading and public hearing
- ☐ 4 weeks notification to municipal officials required prior to public hearing
- ☐ Decreases revenues or increases expenditures without balancing budget
- ☐ Budget required
- ☐ Statement of fiscal impact required
- ☐ Bid waiver requiring County Manager's written recommendation
- ☐ Ordinance creating a new board requires detailed County Manager's report for public hearing
- ☐ Housekeeping item (no policy decision required)
- ☐ No committee review

Approved _____ Mayor
Veto _____
Override _____

Agenda Item No. 6(P)
11-30-04

ORDINANCE NO. _____

ORDINANCE RELATING TO ZONING AND
OTHER LAND DEVELOPMENT REGULATIONS;
PROVIDING FOR THE NARANJA COMMUNITY
URBAN CENTER ZONING DISTRICT; CREATING
SECTIONS 33-284.66 THROUGH 33-284.76 OF THE
CODE OF MIAMI-DADE COUNTY (CODE);
AMENDING SECTIONS 33-311, 33-313 AND 33-314
OF THE CODE; PROVIDING SEVERABILITY,
INCLUSION IN THE CODE AND AN EFFECTIVE
DATE

**BE IT ORDAINED BY THE BOARD OF COUNTY COMMISSIONERS OF MIAMI-
DADE COUNTY, FLORIDA:**

Section 1. Sec. 33-284.66 of the Code of Miami-Dade County, Florida, is hereby created
as follows:¹

>> **ARTICLE XXXIII (J)**

NARANJA COMMUNITY URBAN CENTER DISTRICT

¹ Words stricken through and/or [[double bracketed]] shall be deleted. Words underscored and/or
>>double arrowed<< constitute the amendment proposed. Remaining provisions are now in effect
and remain unchanged.

Sec. 33-284.66. Purpose and applicability.

1. The Comprehensive Development Master Plan (CDMP) contains directives to promote urban centers in places where mass transit, roadways, and highways are highly accessible. The CDMP provides for three types of urban centers: community (CUC), metropolitan (MUC) and regional (RUC). CUCs are a mechanism by which those CDMP directives can be addressed, because CUCs are compact, mixed-use, and pedestrian-friendly areas. In the Naranja CUC area these CDMP directives are intended to be achieved by the following means:
 - A. allocating development intensities within the Naranja CUC according to proximity to mass transit, and by creating Core, Center and Edge sub-districts to allocate the various development intensities within the CUC; and
 - B. by organizing an interconnected network of tree-lined streets and sidewalks to improve pedestrian access to transit, jobs, and shopping; and
 - C. by providing for open space with specific square, green and/or plaza locations, and by shaping the way buildings front onto open space and streets.
2. The regulations contained in this chapter and Chapter 18-A, Code of Miami-Dade County, Florida, shall apply to this article, except as otherwise added to or modified herein.
3. The Illustrative Plan (Figure 1), shall be used to assist in interpreting this article. Where there is conflict between the Illustrative Plan and the text of this article, the text shall govern.
4. The boundaries shown in Figure 1 shall constitute the Naranja CUC Boundary Plan and are generally described as follows: from the northwest corner of the intersection of SW 137 Avenue and SW 272 Street, north along the west side of SW 137 Avenue to the south side of SW 256 Street, then west along the south side of SW 256 Street to the UDB line, as reflected on the maps on file with the Department of Planning and Zoning dated September 22, 2003, then south and west along the UDB to the centerline of SW 149 Avenue, then south along the centerline of SW 149 Avenue to the C-103N canal, then southeast along the canal to the north side of SW 272 Street,

then east along the north side of SW 272 Street to the west side of SW 142 Avenue, then north along the west side of SW 142 Avenue to the south side of SW 270 Street, then east along the north side of SW 270 Street to the east side of the FEC easement, then southeast along the east side of the FEC easement to the north side of SW 272 Street, then east along the north side of SW 272 Street to the west side of SW 137 Avenue. The exact location of the UDB line as of the effective date of this ordinance is on file with the Department of Planning and Zoning. An approximate delineation of the UDB line is depicted in the Regulating Plans. Any amendment to the CDMP resulting in a movement of the UDB line following the effective date of this ordinance shall be followed by an amendment to this section of the code to reflect the new UDB line or the westernmost boundaries of the NCUC in compliance with the half-a-mile radius CDMP requirement for Community Urban Centers.



A more detailed legal description of the boundaries follows:

Begin at the NE corner of the SE ¼ of Section 27-56-39. Thence W. along the centerline of SW 256 St for a distance of 1877' + to the centerline of State Hwy. #5. Thence SW/ly along the centerline of State Hwy. #5 for 285'+/- to a point. Thence N47°-04'-12"W for 300'+/- to the centerline of SW 256 St. Thence W. along SW 256 St. centerline for 1600'+/- to a point. Thence S40°34'07"W for 2380'+/- to the theoretical W/ly R/wy of SW 147 Ave. Thence S. along the theoretical W/ly R/wy of SW 147 Avenue for 850' +/- to the N/ly R/wy of SW 264 St. Thence W. along the N/ly line of SW 264 St. for 1287'+/- to theoretical centerline of SW 149 Ave. Thence S. along SW 149 Ave for 1030'+/- to the N/ly R/wy of Canal C-103 N. Thence SE/ly along the N. line of canal for 2450'+/- to the centerline of SW 272 St. Thence E. along SW 272 St centerline for 2340'+/- to the centerline of SW 142 Ave. Thence N. along 142 Ave for 682'+/- to the centerline of SW 270 St. Thence E. for 1050'+/- to the W/ line of FEC EASEMENT. Thence SE/ly along the W. line of FEC EASTMENT 895'+/- to the centerline of SW 272 St. Thence E. 1080'+/- to SW 137 Ave. Thence N. along 137 Ave for a distance of 5280'+/- to the point of beginning.

Full scale maps of the Illustrative Plan presented in Figure 1, as well as all the Regulating Plans and Street Development Parameters figures in this article, are on file with the Miami-Dade Department of Planning and Zoning.

5. No provision in this article shall be applicable to any property except lands lying within the boundaries of the Naranja Community Urban Center District as described herein. No property lying within the boundaries of the Naranja Community Urban Center shall be entitled to the uses or subject to the regulations provided in this article until an application for a district boundary change to the Naranja Community Urban Center District has been heard and approved in accordance with the provisions of this chapter.

Figure 1: Illustrative Master Plan



CUC Boundary Plan

Section 2. Sec. 33-284.67 of the Code of Miami-Dade County, Florida, is hereby created as follows:

Sec. 33-284.67. Definitions.

Terms used throughout this Article shall take their commonly accepted meaning unless otherwise defined in Chapters 18-A, 28 or 33 of the Code of Miami-Dade County. Terms requiring interpretation specific to this Article are as follows:

1. *Anchor point*: the location depicted on the Open Space Plan on which some portion of a plaza, green, or square must be situated.

2. *Bike lane*: a corridor dedicated specifically for bicycle use.

3. *Block*: a combination of building lots, the perimeter of which abuts public rights-of-way or an open space.

4. *Block face*: the right-of-way line or easement line that delineates a block edge.

5. *Boulevard*: a roadway traversing a neighborhood, flanked with sidewalks, on-street parking, street trees and buildings.

6. *Building height*: definition provided in section 33-1(17) of the code. In addition, building height shall not apply to clock towers, cupolas, chimneys, or church steeples and shall be in accordance with the Street Type Development Parameters.

7. *Build-to line*: a line parallel to the block face, along which a building shall be built. A forecourt may be used to vary the build-to line in the Core and Center sub-districts.

8. *Busway*: a limited access right of way for the exclusive use of buses.

9. *Civic use*: civic uses in this zoning district shall be in compliance with section 33-284.51(B) of this code.

10. *Clear zone*: an area within the curb radius, which shall be kept clear of all objects to a prescribed height to provide vehicle clearance.


11. Colonnade: a roofed structure, extending over a private walkway, open to the street and sidewalk except for supporting columns or piers. Colonnades shall have a minimum clear height of ten (10) feet (including lighting) and a minimum clear width of ten (10) feet (on the first floor from build-to line to exterior building face excluding supporting structures). Awnings are permitted but shall not count towards the required colonnades. Colonnades shall not cause roof drainage into the public right-of-way. Colonnades shall be attached to buildings.

12. Cornice line: a molded and projecting horizontal member that crowns an architectural composition. A cornice line shall project a minimum of 2 inches from the front elevation of the structure.

13. Designated open space: an outdoor, at grade space, including greens, squares, plazas and colonnades as indicated on the Designated Open Space Plan.

14. Fenestration: design and position of windows, entrances, and other structural openings in a building.


15. Forecourt: the space between the principal building and the right-of-way where the building façade is set back and replaced by a low wall at the frontage line. The forecourt is suitable for gardens and outdoor seating and is required to be fronted by buildings on three sides.



Forecourt

16. Front property line: the property line abutting the higher ranking street right-of way. For equal ranking street rights-of-way, either frontage shall be the front property line.

17. Green: an outdoor open space, mostly surrounded by residential uses, that shall not be hard surfaced for more than 20 percent of the area exclusive of dedicated rights-of-way. Greens shall be located according to the Designated Open Space Plan. Its landscaping shall consist primarily of lawn, trees and garden structures.



Green

18. Greenway or linear park: an outdoor open space along a natural edge, such as a river front, a canal, a scenic road, or other route. Greenways provide passage for pedestrians or bicycles and are used to link nature reserves, cultural features, other parks and open spaces and/or historic sites.

19. Habitable space: building space whose use involves regular human presence with direct view of the streets, service roads or open space on which it fronts. Habitable space shall not include parking garages, self-service storage facilities, or warehouses.

20. Home office: an allowed professional office use within a residential use as provided in section 33-284.68 of this code.

21. Irregularly shaped lot: a lot in areas designated Residential (R) and Residential Modified (RM) with an irregular shape due to its location on a corner or intersection or at the end of a grouping of single-family detached or attached units. The dimensions of the front yard of such lot shall be similar to the dimensions of the front yards of adjacent homes.

22. Live-work unit: a mixed-use building type with one single-family residential dwelling located above a single work space.

23. Main street: a vehicular and pedestrian thoroughfare lined primarily with mixed-use buildings as depicted on the Street Types Regulating Plan.

24. Minor street: a street predominantly residential in character as depicted on the Street Types Regulating Plan.

25. Mixed-use building: a building that includes a combination of two or more uses, such as retail and/or office, on the ground floor, with residential above.


26. Off-street parking: garage parking or surface parking not on a public or private street.

27. On-street parking: parking on a public or private street.

28. Outdoor produce market: an outdoor commercial establishment where produce and hand crafted items are offered for sale.

29. Pedestrian passages: interconnected paved walkways that provide pedestrian passage through blocks and that connect directly with the network of sidewalks and open spaces.

30. Plaza: an outdoor open space on which retail and office uses front. A minimum of 50 percent and a maximum of 75 percent of the plaza's area, exclusive of dedicated rights-of-way, shall be hard surfaced. Plazas shall be located according to the Designated Open Space Plan. Its landscaping shall consist primarily of hard surfaced areas, permanent architecture or water-oriented features, and trees that are placed in an orderly fashion and that are regularly spaced as shown below.




Plaza

31. Rowhouse: a single-family attached dwelling unit of a group of 3 to 7 units, each separated from the adjoining unit by a common party fire wall. A minimum space of 15 feet between building groups shall be provided. Each common party fire wall shall extend to the roof line or above the roof of units that it serves and shall have no openings therein. Each rowhouse unit shall be constructed upon a separate platted lot. Each rowhouse unit shall be serviced with separate utilities and shall otherwise be independent of any other unit.

32. Service road: a private or public vehicular passageway providing primary, secondary, or service access to the sides or rear of building lots.

33. *Square*: an outdoor open space that shall be flanked by streets on at least 3 sides and shall not be hard surfaced for more than 50 percent of the area exclusive of dedicated rights-of-way. Squares shall be located according to the Designated Open Space Plan. Its landscaping shall consist primarily of hard surfaced walks, lawns, and trees that are placed in an orderly fashion and that are regularly spaced as shown below.



Square

34. *Storefront*: the portion of a building at the first story of a frontage that is made available for retail use.

35. *Street network*: a system of intersecting and interconnecting streets and service roads.

36. *Street vista*: a view through or along a street centerline with a termination of a significant visual composition of an architectural structure or element placed in the view. Garages and blank walls are not significant visual compositions.

37. *Weather protection elements*: architectural elements that provide protection from the sun and the rain, such as colonnades, awnings, bus shelters, or projecting roofs.

Section 3. Sec. 33-284.68 of the Code of Miami-Dade County, Florida, is hereby created as follows:

Sec. 33-284.68. Uses.

No land, body of water, or structure shall be used or permitted to be used and no structure shall be hereafter erected, constructed, reconstructed, moved, structurally altered, or maintained for any purpose in the Naranja Community Urban Center (NCUC) District except as provided in this article. The uses delineated herein shall be permitted only in compliance with the Regulating Plans and General Requirements provided in this article.

A. Permitted Uses.

1. Residential uses.

- a. Residential uses are permitted in the areas designated in the Land Use Regulating Plan as Residential (R), Residential Modified (RM), Mixed-Use U.S. 1 (M1), and Mixed-Use Main Street (MM) as provided in the table below. Limited residential uses are also permitted in areas designated Industrial District (ID), pursuant to sub-paragraph (3) and the table below.

<u>Land Use Areas</u>					<u>Permitted Residential Uses</u>
<u>R</u>	<u>RM</u>	<u>M1</u>	<u>MM</u>	<u>ID</u>	
<u>X</u>					<u>detached single family dwelling</u>
<u>X</u>	<u>X</u>				<u>duplex</u>
<u>X</u>	<u>X</u>				<u>rowhouse</u>
<u>X</u>	<u>X</u>				<u>family day care (upon compliance with the applicable requirements of the RU-1 zoning district regulations)</u>
<u>X</u>	<u>X</u>				<u>group home (upon compliance with the applicable requirements of the RU-1 zoning district regulations)</u>
<u>X</u>	<u>X</u>				<u>municipal recreation building, playground or park owned and operated by a municipality, county, state, or the federal government</u>
<u>X</u>	<u>X</u>				<u>public assembly uses: only on sites no greater than three acres and only in accordance with the Street Types Development Parameters. Parking for public assembly uses shall be provided in compliance with section 33-284.51(B)(4).</u>
	<u>X</u>	<u>X</u>	<u>X</u>		<u>Multiple family apartment units are permitted in RM and when vertically integrated with other lawful uses in M1 and MM.</u>
				<u>X</u>	<u>Limited residential uses are permitted in areas designated Industrial District (ID), pursuant to sub-paragraph (3) below.</u>
<u>(X) permitted in the Land Use Area</u>					

- b. The following uses are permitted in the rear as ancillary uses to a lawful residential unit in the areas designated Residential (R) and Residential Modified (RM):

- (1) the following accessory buildings and uses (non-habitable): workshop, garage, utility shed, gazebo, cabanas, garden features, basketball hoops and carports which uses shall not count against required open space.

- (2) for a detached single family dwelling or rowhouse unit only, a single accessory dwelling unit of no more than 600 square feet of habitable space under the same ownership as the primary structure
- (3) home office

2. Mixed uses.

a. The following uses are permitted in a structure located in the areas designated in the Land Use Regulating Plan as Mixed-Use Main Street (MM) and Mixed-Use U.S. 1 (M1) in accordance with the provisions of the Land Use Regulating Plan. All structures in the MM and M1 areas shall provide at least the minimum residential component as per the Land Use Regulating Plan.

- (1) Multiple family apartment units are permitted when vertically integrated with other lawful uses, in the areas designated in the Land Use Regulating Plan as Mixed-Use Main Street (MM) and Mixed-Use U.S. 1 (M1)
- (2) professional offices as allowed in the RU-5 zoning district
- (3) civic uses
- (4) schools
- (5) governmental offices
- (6) hotels and apartment hotels
- (7) the following business uses:

antique shops

apparel store new and used merchandise, provided such establishments contain no more than 4,000 square feet of gross floor area

appliance and electrical fixture stores

art goods stores, artist studios, galleries, and museums

auditoriums, convention halls, and theaters

bait and tackle shops

banks, excluding drive-in teller services

banquet halls and convention halls

beauty parlors

bakeries

barber shops

bicycle sales, rentals, and repairs (non-motorized)

billiard rooms

card shops and book stores
confectionary, ice cream stores, and dairy stores
conservatories and music and dance studios
dairy stores
department stores, provided such establishments contain no more than
40,000 square feet of ground floor area
drugstores
dry-cleaning establishments where cleaning is not done onsite, offering
drop-off and pick-up service only, but allowing other services such as
clothing alterations, tailoring and shoe repair, provided such
establishments contain no more than 4,000 square feet of floor area
florist shops and garden shops
furniture stores and upholstery shops
grocery stores, fruit stores, health food stores, delicatessen, meat and fish
markets, and other similar food stores
handcrafted products shops and hobby shops, including related workshops
hardware stores
health and exercise clubs
information booths
interior design shops
jewelry stores
leather goods and luggage shops
locksmith
mail order offices, without storage of products sold
meeting halls
movie theaters (not including drive-in theaters)
municipal recreation buildings
newsstands
night clubs
office and stationery supplies
optical stores
paint and wallpaper stores
photography studios, photo supply shops, and photo galleries
physical training schools with indoor training facilities up to 5,000 square
feet in size, such as, but not limited to, gymnastics, martial arts, and
dance academies
police and fire substations

post office

pottery shops

printing shops

schools

libraries

transit stations

pubs and bars provided that these establishments comply with the distance requirements in section 33-150 of this code as they apply to schools and churches only

religious facilities

restaurants, coffee houses. Outdoor table service and outside walk-up window service in conjunction with restaurants and coffee houses may be provided with the following requirements:

a. The restaurant furniture located on the sidewalk shall maintain a minimum five-foot wide obstacle-free corridor for pedestrian circulation along the sidewalk and shall be stored inside the property during nonoperating hours.

b. Alcoholic beverages may be served outdoors only where such service is strictly incidental to the service of food.

c. No drive-through restaurants are permitted.

second hand stores and flea markets (inside building only)

shoe stores and shoe repair shops

souvenir shops and gift shops

sporting goods stores

tailor shops

tobacco shops

variety stores.

b. On the east side of U.S. 1, Residential Modified (RM) lots abutting designated Mixed Use U.S. 1 (M1) lots on at least one side, are allowed to have uses permitted in the M1 area for a depth from U.S. 1 not to exceed that of the M1 lots.

3. Industrial uses.

The following uses are permitted in the Industrial District (ID) area:

These uses shall be allowed in conformance with the Land Use Regulating Plan and the Street Types Development Parameters.

- a. all uses permitted in the IU-1 zoning district
- b. all uses permitted in the IU-C zoning district after public hearing pursuant to section 33-311(A)(3) of this code
- c. In any sub-district, live-work units with the following permitted uses:
 - a single-family residential unit in connection with one of the following permitted uses for its workshop area:
 - antique shops
 - art goods stores, artist studios, galleries
 - artisanal use
 - bait and tackle shops
 - bakeries
 - cabinet shops
 - dance studios
 - dry cleaning and dyeing establishments
 - engines, sales and service
 - glass installation
 - health and exercise clubs
 - interior design shop
 - leather goods manufacturing, excluding tanning
 - locksmith shops, sharpening and grinding shops
 - mail order offices and storage
 - office use
 - photography labs
 - pottery shops
 - printing shops
 - rare books sales
 - restaurants, excluding drive-through service
 - secondhand stores
 - shoe stores and shoe repair shops
 - upholstery and furniture shops
 - veterinarian and air conditioned pet hospital
 - wholesales salesrooms
- d. the following limited residential uses are permitted on the following conditions: (1) when buffered by a street, a service road or live-work units, and (2) when fronting an "A" Street:

1. in the Edge sub-district, the residential uses permitted in the Residential (R) areas at a minimum density of 8 dwelling units per acre net to a maximum density of 18 dwelling units per acre net
2. in the Center sub-district, the residential uses permitted in the Residential Modified (RM) areas at a minimum density of 12 dwelling units per acre net to a maximum density of 36 dwelling units per acre net
- e. in the Core and Center sub-districts only, on lots fronting on US 1, all uses permitted in Mixed-Use U.S.1 (M1) at a minimum residential density of 12 dwelling units per acre net to a maximum density of 52 dwelling units per acre net without the use of Severable Use Rights (SUR's) or a maximum density of 60 dwelling units per acre net with the use of SUR's
- f. in the Edge and Center sub-districts, except for properties along US 1, automobile service stations when in compliance with the requirements of paragraph (B)(3) below
- g. in the Edge and Center sub-districts, except for properties along US 1, drive-through facilities when in compliance with the requirements of paragraph (B)(4) below

4. Market District uses.

The following uses are permitted in the Market District (MD) areas:

These uses shall be allowed in conformance with the Land Use Regulating Plan and the Street Types Development Parameters.

- a. outdoor produce markets, and
- b. all uses permitted in the Mixed-Use U.S. 1 (M1) except for residential.

B. Conditionally Permitted Uses.

The following land uses are permitted upon approval by the Director of a site plan and any accompanying plans necessary to assure compliance with the requirements established herein:

1. Bed and breakfast inn: a single-family dwelling unit used as a bed and breakfast inn shall be permitted in the Residential Modified (RM) and Residential (R) areas only when it is demonstrated that:
 - a. The dwelling unit has a minimum air conditioned floor area of 2,000 square feet.
 - b. Each bedroom of the dwelling unit is a minimum of 150 square feet.
 - c. The dwelling unit is owner-occupied.
 - d. All required parking for the dwelling unit is located at the rear of the dwelling unit, provided that where on-street parking is permitted it is located in front of the lot. A minimum of one space per rentable room of lodging is required. Two parking spaces are required for owner/operator.
2. The sale of alcoholic beverages, including but not limited to liquor or package stores, shall be permitted only in the MM, M1, MD and ID areas in the Core sub-district and only in compliance with the applicable requirements of section 33-150 of this code pertaining to spacing from schools and churches only.
3. An automobile service station shall be permitted only in the Industrial District (ID) areas in the Edge and Center sub-districts and shall be exempt from the minimum height requirement, and shall provide a continuous street façade consisting of buildings or walls along all rights-of-way except driveways. Walls, if provided, shall not exceed 3'-6" in height, shall be a minimum of 75 percent transparent so as not to preclude visibility for drivers, and shall not exceed 60 percent of the length of the frontage.
4. Drive-through facilities shall be permitted only in the Industrial District (ID) areas in the Edge and Center sub-districts, and shall provide a continuous street façade consisting of buildings or walls along all rights-of-way except driveways. Walls, if provided, shall not exceed 3'-6" in height, shall be a minimum of 75 percent transparent so as not to preclude visibility for drivers, and shall not exceed 60 percent of the length of the frontage.

C. Temporary Uses.

The following temporary structures and uses shall be permitted:

1. Construction trailers used in conjunction with construction projects, when located at a building site where there is a valid building permit for the construction project, or, in the case of a residential subdivision, a valid building permit for at least one of the residential units being constructed. All construction trailers shall be located at least 10 feet from all street rights-of-way.
2. At any construction site where there is a valid building permit, one or more security guard houses may be installed. Use of such structures may include overnight stay provided adequate sanitary facilities are provided and the same requirements as for construction trailers are met.
3. Uses of less than 45 days' duration and occurring no more than 3 times per year at a particular location, and only when associated with a permanent use, shall apply for a seasonal permit. Upon completion and submittal of an application, the Director of the Department of Planning and Zoning shall grant a seasonal permit for the temporary uses such as Christmas trees sales, pumpkin sales, firework sales, and shows for civic and youth organizations.

Section 4. Sec. 33-284.69 of the Code of Miami-Dade County, Florida, is hereby created as follows:


Sec. 33-284.69. Regulating Plans.

The Regulating Plans consist of the following controlling plans as defined and graphically depicted in this section.









- a. The Street Types Plan establishes a hierarchy of street types in existing and future locations that shall be provided and shown in all development plans. The five (5) Street Types and the hierarchy of streets (from most important to least important in accommodating pedestrian traffic) are U.S. 1, Boulevard, Main Street, Minor Street, and Service Road.
- b. The Sub-districts Plan delineates three (3) sub-districts: the Core, Center and Edge. These sub-districts regulate the allowable intensity of development in accordance with the Comprehensive Development Master Plan and this article.
- c. The Land Use Plan delineates the areas where specified land uses and development of various types and intensities will be permitted.

- d. The Building Heights Plan establishes the minimum and maximum allowable number of floors.
- e. The Designated Open Space Plan designates open spaces, which shall be shown in all development plans. The designated open spaces are controlled by anchor points.
- f. The New Streets Plan shows the location and the number of new streets needed to create the prescribed network of streets within the NCUC District. All new A streets are required in the same general location as shown on the New Streets Plan. All B streets shall be located as provided in section 33-284.71(F) of this code.
- g. The Bike Route Plan depicts the designated bike routes, which shall be shown in all development plans.

I. Street Types Plan




KEY





-  US Highway 1 / S.R. 5
-  South Miami-Dade Busway
-  Main Street
-  Boulevard
-  Minor Street
-  Service Roads
Core/Center Sub-district
-  Service Roads
Edge Sub-district: Optional for single family detached only
-  Urban Development Boundary



II. Sub-districts Plan




KEY

-  Core Sub-District
 Center Sub-District
 Edge Sub-District
 Urban Development Boundary





23





III. Land Use Plan

See Section 33-284.68 on this Code for specific permitted uses in each land use area.




KEY

-  **MM: Mixed-use (Main Street):** 1st floor - businesses, professional offices, civic, education and government offices; 2nd floor and above - residential; and live-work units (Min. 12 units/acre net, Max. 52 units/acre net without the use of SUR* or a Max. 60 units/acre net with the use of SUR*)
-  **M1: Mixed-use U.S.1:** minimum 1 floor - residential; all other floors - businesses, professional offices, civic, education and government offices; and live-work units (Min. 12 units/acre net, Max. 52 units/acre net without the use of SUR* or a Max. 60 units/acre net with the use of SUR*)
-  **RM: Residential Modified:** Duplex, row-house and small apartments (Min. 12 units/acre net, Max. 36 units/acre net)
-  **R: Residential:** Single family detached, duplex and rowhouse dwellings (Min. 8 units/acre net, Max. 18 units/acre net)


-  **MD: Market District:** all floors - outdoor produce markets are permitted. In addition, all uses permitted in the Mixed-use U.S.1 (M1) except for residential are allowed.
-  **ID: Industrial District:** in all floors and all Sub-districts - IU-C uses and live-work units. In addition, for properties facing US1 in the Core and Center Sub-districts, all uses permitted in the Mixed-use Special/Single Use; in the Center Sub-district, all uses and density permitted in the Residential Modified (RM); and in the Edge Sub-district, all uses and density permitted in the Residential (R) are allowed as per Sec. 33-284.68 A3.
-  **I: Institutional:** Civic, education and government offices. Community center is designated to be publicly developed. If community center is privately developed then the Mixed-use (Main Street) criteria shall apply.
-  **Urban Development Boundary**

* SUR: Severable Use Right when and to the extent permitted by sections 33B-41 to 33B-47 of this code.

IV. Building Heights Plan



V. Designated Open Space Plan



KEY



Open Space: G: Green; S: Square;
P: Plaza



Existing Water Bodies



Street Vista



Anchor Point



Urban Development Boundary


No	Type	Area
1.	S	15,000 sqft
2.	S	17,000 sqft
3.	G	32,200 sqft
4.	G	28,000 sqft
5.	G	25,000 sqft
6.	P	10,000 sqft
7.	P	5,000 sqft
8.	G	Existing
9.	S	50,200 sqft
10.	P	5,400 sqft
11.	P	7,000 sqft
12.	G	9,600 sqft
13.	G	120,500 sqft
14.	G	35,000 sqft
15.	G	2,600 sqft
16.	G	7,000 sqft
17.	G	4,000 sqft
18.	G	18,000 sqft

An open space where an anchor point is shown shall provide the general square footage shown in this Designated Open Space Plan.


An open space where an anchor point is not shown shall be developed according to the Street Type Development Parameters.

Moody Drive (SW 268 Street) green in the Center Sub-District (number 15) may be developed residentially under the RM criteria or business under the M1 or MD criteria and shall be developed according to the Open Space Regulations.








VI. Bike Route Plan



VII. New Streets Plan



KEY

-  New "A" Streets
-  Existing "A" Streets
-  New "B" Streets
-  Existing "B" Streets
-  Streets to be Removed
-  Urban Development Boundary
-  Property Ownership Pattern at time of charrette



Section 5. Sec. 33-284.70 of the Code of Miami-Dade County, Florida, is hereby created as follows:

Sec. 33-284.70. Street Type Development Parameters.

The following diagrams establish design parameters based on street type and Sub-district.

U.S. HIGHWAY 1/S.R. 5 CORE	
STREET SECTION US-1 R.O.W.: 116' Building Height: Min: 3 stories Max: 6 stories Market District: Max: 2 stories when developed as a produce market KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	<p>* Note: Actual dimensions of South Miami-Dade Busway extension shall take precedence over dimensions depicted here.</p>
BUILDING PLACEMENT Key: — Build to Line --- Property Line [Shaded Box] Required Colonnade [Diagonal Lines Box] Habitable Space [Stippled Box] Parking and/or allowable building area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	100 Percent at build-to line.
PARKING	All on-site parking shall be accessed from the service road or adjacent minor street. On-street parking shall count towards the minimum required parking. Up to 60% of required parking may be provided off site within a 500' radius.
LANDSCAPE/ OPEN SPACE	Parking lot buffers and street trees shall meet all requirements of Chapter 18-A of this Code and this Article except street trees shall have a minimum diameter breast height of 4". Street trees shall be planted in an 8' min. continuous landscape strip. Permanent irrigation is required.
SETBACK	The front, side, and rear setback shall be as shown above.
OTHER ELEMENTS	A colonnade shall be required on both sides of U.S. 1, in the Core Sub-district, when the build-to line is 0' and shall occupy the full length of the building frontage. The above section is typical for all busway and US-1 frontages. For all development along Old Dixie Highway the right-of-way, building placement, and frontage requirements shall be the same as for the development adjacent to the busway. * Note is inserted to depict rounded off dimensions of the Busway. It will not change required dedication.

U.S. HIGHWAY 1/S.R. 5 CENTER	
STREET SECTION US-1 R.O.W.: 116' Building Height: Min: 3 stories Max: 6 stories Market District: Max: 2 stories when developed as a produce market KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	<p>* Note: Actual dimensions of South Miami-Dade Busway extension shall take precedence over dimensions depicted here.</p>
BUILDING PLACEMENT Key: — Build to Line --- Property Line Hatched Area: Habitable Space Hatched Area: Parking and/or allowable building area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	80 Percent Minimum at build-to line.
PARKING	All on-site parking shall be accessed from the service road or adjacent minor street. On-street parking shall count towards the minimum required parking except for single family attached and detached residential uses. Up to 60% of required parking may be provided off site within a 500' radius.
LANDSCAPE/ OPEN SPACE	Parking lot buffers and street trees shall meet all requirements of Chapter 18-A of this Code and this Article except street trees shall have a minimum diameter breast height of 4". Street trees shall be planted in an 8' min. continuous landscape strip. Permanent irrigation is required.
SETBACK	The side setback shall be 0' or 6' in order to implement urban design principles. The front and rear setback shall be as shown above.
OTHER ELEMENTS	The front setback shall be hard surfaced and weather protection elements provided on the building facade when the build-to line is 10' from the front property line. Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements. The above section is typical for all busway and US-1 frontages. * Note is inserted to depict rounded off dimensions of the Busway. It will not change required dedication.

U.S. HIGHWAY 1/S.R. 5	
EDGE	
STREET SECTION US-1 R.O.W.: 116' Building Height: Min: 2 stories Max: 4 stories Market District: Max: 2 stories when developed as a produce market KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	<p>* Note: Actual dimensions of South Miami-Dade Busway extension shall take precedence over dimensions depicted here.</p> <p>Diagram showing the street section with Frontage Rd (36' R.O.W.), BUSWAY (100' R.O.W.), and US1 (116' R.O.W.). The diagram includes dimensions for various lanes, medians, and setbacks.</p>
BUILDING PLACEMENT Key: — Build to Line --- Property Line Hatched Area: Habitable Space Hatched Area: Parking and/or allowable building area	<p>Diagram showing building placement with setbacks: 0' or 6' setback, 10' or 15' setback, 20' min, and 0' or 6' setback. The diagram also shows the building footprint and the service road.</p>
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	80 Percent Minimum at build-to line.
PARKING	All on-site parking shall be accessed from the service road or adjacent minor street. On-street parking shall count towards the minimum required parking except for single family attached and detached residential uses.
LANDSCAPE/ OPEN SPACE	Parking lot buffers and street trees shall meet all requirements of Chapter 18-A of this Code and this Article except street trees shall have a minimum diameter breast height of 4". Street trees shall be planted in an 8' min. continuous landscape strip. Permanent irrigation is required.
SETBACK	The front setback shall be 10' or 15' and the side setback shall be 0' or 6' in order to implement urban design principles. The rear setback shall be as shown above.
OTHER ELEMENTS	<p>The front setback of buildings along US1 shall be hard surfaced and weather protection elements provided on the building facade when the build to line is 10' from the front property line. When the build to line is 15' from the front property line, the remainder 5' shall be landscaped.</p> <p>The front setback of buildings along the busway shall be landscaped.</p> <p>Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements.</p> <p>The above section is typical for all busway and US-1 frontages.</p> <p>* Note is inserted to depict rounded off dimensions of the Busway. It will not change required dedication.</p>

MAIN STREET (SW 264th Street East of US1) CORE	
STREET SECTION R.O.W.: 90' Building Height: Min: 3 stories Max: 6 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line --- Property Line ▨ Required Colonnade ▨ Habitable Space ▨ Parking and/or allowable building area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	100 Percent Minimum at build-to line.
PARKING	All on-site parking shall be accessed from the service road. On-street parking shall count towards the minimum required parking. Up to 60% of required parking may be provided off site within a 500' radius.
LANDSCAPE/ OPEN SPACE	Parking lot buffers and street trees shall meet all requirements of Chapter 18-A of this Code and this Article except street trees shall have a minimum diameter breast height of 4". Permanent irrigation is required. Street trees are optional but if provided, shall be planted in 5'x5' tree grates.
SETBACK	The front, side, and rear setback shall be as shown above.
OTHER ELEMENTS	A colonnade shall be required on both sides of the Main Street when build-to line is 0' and shall occupy the full length of the building frontage. Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements. On all Main Street intersections, the median shall have a mountable curb.

MAIN STREET (SW 264th Street East of US1)	
CENTER	
STREET SECTION R.O.W.: 70' Building Height: Min: 2 stories Max: 4 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line --- Property Line Hatched Area: Habitable Space Dotted Area: Parking and/or allowable building area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	80 Percent Minimum at build-to line.
PARKING	All on-site parking shall be accessed from the service road. On-street parking shall count towards the minimum required parking except for single family attached and detached residential uses. Up to 60% of required parking may be provided off site within a 500' radius.
LANDSCAPE/ OPEN SPACE	Parking lot buffers and street trees shall meet all requirements of Chapter 18-A of this Code and this Article except street trees shall have a minimum diameter breast height of 4". Street trees shall be planted in 5' x 5' tree grates. Permanent irrigation is required.
SETBACK	The side setback shall be 0' or 6' in order to implement urban design principles. The front and rear setback shall be as shown above.
OTHER ELEMENTS	The front setback shall be hard surfaced and weather protection elements provided on the building facade when the build-to line is 10' from the front property line. Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements.

MAIN STREET (SW 264th Street East of US1)	
EDGE	
STREET SECTION R.O.W.: 70' Building Height: Max: 2 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line --- Property Line Hatched Area: Habitable Space Cross-hatched Area: Accessory Bldg/Dwelling or Parking Area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	60 percent minimum at build-to line. For single family attached only, 100 percent at build-to line.
PARKING	For single family attached, all on-site parking shall be accessed from the service road.
LANDSCAPE/ OPEN SPACE	Landscape shall meet all requirements of Chapter 18-A of this Code and this Article. Street trees shall be planted in a 5' minimum continuous landscape strip
SETBACK	The front setback shall be 10' or 15' in order to implement urban design principles. The side and rear setbacks shall be as shown above.
OTHER ELEMENTS	The front setback shall be landscaped. Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements.

36

BOULEVARD	
CORE	
STREET SECTION R.O.W.: Varies Building Height: Min: 3 stories Max: 6 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line --- Property Line Required Colonnade Habitable Space Parking and/or allowable building area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	100 Percent at build-to line.
PARKING	All on-site parking shall be accessed from the service road. On-street parking shall count towards the minimum required parking. Up to 60% of required parking may be provided off site within a 500' radius.
LANDSCAPE/ OPEN SPACE	Parking lot buffers and street trees shall meet all requirements of Chapter 18-A of this Code and this Article except street trees shall have a minimum diameter breast height of 4". Permanent irrigation is required.
SETBACK	The front, side, and rear setbacks shall be as shown above.
OTHER ELEMENTS	A colonnade shall be required on both sides of the boulevard when build-to line is 0' and shall occupy the full length of the building frontage. Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements. On all Boulevard intersections, the median shall have a mountable curb.

<div>BOULEVARD</div> <div>CENTER (A) MIXED-USE</div>	
STREET SECTION R.O.W.: Varies Building Height: Min: 2 stories Max: 4 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line - - - Property Line Hatched Area: Habitable Space Dotted Area: Parking and/or allowable building area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	80 Percent Minimum at build-to line.
PARKING	All on-site parking shall be accessed from the service road. On-street parking shall count towards the minimum required parking. Up to 60% of required parking may be provided off site within a 500' radius.
LANDSCAPE/ OPEN SPACE	Parking lot buffers and street trees shall meet all requirements of Chapter 18-A of this Code and this Article except street trees shall have a minimum diameter breast height of 4". Street trees shall be planted in 5' x 5' tree grates. Permanent irrigation is required.
SETBACK	The side setback shall be 0' or 6' in order to implement urban design principles. The front and rear setbacks shall be as shown above.
OTHER ELEMENTS	The front setback shall be hard surfaced and weather protection elements provided on the building facade when the build-to line is 10' from the front property line. Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements. On all Boulevard intersections, the median shall have a mountable curb.

BOULEVARD CENTER (B) RESIDENTIAL	
STREET SECTION R.O.W.: Varies Building Height: Min: 2 stories Max: 4 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line --- Property Line Hatched Area: Habitable Space Cross-hatched Area: Accessory Building/Dwelling or Parking Area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	75 percent minimum at build-to line. For single family attached only, 100 percent at build-to line.
PARKING	All on-site parking shall be accessed from the service road. On-street parking shall count towards the minimum required parking except for single family attached and detached residential uses.
LANDSCAPE/ OPEN SPACE	Parking lot buffers and street trees shall meet all requirements of Chapter 18-A of this Code and this Article except street trees shall have a minimum diameter breast height of 4". Street trees shall be planted in a 5' minimum continuous landscape strip. Permanent irrigation is required.
SETBACK	The front setback shall be 0' or 10' in order to implement urban design principles. The side and rear setbacks shall be as shown above.
OTHER ELEMENTS	The front setback shall be landscaped. Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements. For rowhouses, the side setback shall be 0' and for all other residential uses the side setback shall be 6'. On all Boulevard intersections, the median shall have a mountable curb.

BOULEVARD	
EDGE	
STREET SECTION R.O.W.: Varies Building Height: Max: 2 stories KEY: s: sidewalk g: green c: curb and gutter In: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line --- Property Line Hatched Area: Habitable Space Cross-hatched Area: Accessory Building/Dwelling or Parking Area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	60 percent minimum at build-to line. For single family attached only, 100 percent at build-to line.
PARKING	For single family attached all on-site parking shall be accessed from the service road.
LANDSCAPE/ OPEN SPACE	Landscape shall meet all requirements of Chapter 18-A of this Code and this Article. Street trees shall be planted in a 7' minimum continuous landscape strip.
SETBACK	The front setback shall be 10' or 15' in order to implement urban design principles. The side and rear setbacks shall be as shown above.
OTHER ELEMENTS	The front setback shall be landscaped. Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements. On all Boulevard intersections, the median shall have a mountable curb.

MINOR STREET (With two parking lanes)	
CORE	
STREET SECTION R.O.W.: 62' or 70' Building Height: Min: 3 stories Max: 6 stories Market District: Max: 2 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line --- Property Line ▨ Required Colonnade ▨ Habitable Space ▨ Parking and/or allowable building area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	100 Percent Minimum at build-to line.
PARKING	All on-site parking shall be accessed from the service road or minor street. On-street parking shall count towards the minimum required parking. Up to 60% of required parking may be provided off site within a 500' radius.
LANDSCAPE/ OPEN SPACE	Parking lot buffers and street trees shall meet all requirements of Chapter 18-A of this Code and this Article except street trees shall have a minimum diameter breast height of 4". Permanent irrigation is required. Street trees shall be planted in 5' x 5' tree grates.
SETBACK	The front, side, and rear setbacks shall be as shown above.
OTHER ELEMENTS	Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements.

MINOR STREET (With two parking lanes)	
CENTER	
STREET SECTION R.O.W.: 62' or 70' Building Height: Min: 2 stories Max: 4 stories Market District: Max: 2 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line - - - Property Line Hatched Area: Habitable Space Cross-hatched Area: Accessory Building/Dwelling or Parking Area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	75 percent minimum at build-to line. For single family attached only, 100 percent at build-to line.
PARKING	All on-site parking shall be accessed from the service road. On-street parking shall count towards the minimum required parking except for single family attached and detached residential uses.
LANDSCAPE/ OPEN SPACE	Parking lot buffers and street trees shall meet all requirements of Chapter 18-A of this Code and this Article except street trees shall have a minimum diameter breast height of 4". Permanent irrigation is required. Street trees shall be planted in a 5' minimum continuous landscape strip.
SETBACK	The front setback shall be 0' or 10' in order to implement urban design principles. The side and rear setbacks shall be as shown above.
OTHER ELEMENTS	Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements. The front setback shall be landscaped.

42

MINOR STREET (With two parking lanes)	
EDGE	
STREET SECTION R.O.W.: 62' or 70' Building Height: Max: 2 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line - - - Property Line Hatched Area: Habitable Space Cross-hatched Area: Accessory Building/Dwelling or Parking Area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	40 Percent Minimum at build-to line.
PARKING	All on-site parking shall be accessed from the service road where provided. On-street parking shall count towards the minimum required parking except for single family attached and detached residential uses.
LANDSCAPE/ OPEN SPACE	Landscape shall meet all requirements of Chapter 18-A of this Code and this Article. Street trees shall be planted in a 7' minimum continuous landscape strip.
SETBACK	The front setback shall be 10' or 15' in order to implement urban design principles. The side and rear setbacks shall be as shown above.
OTHER ELEMENTS	Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements. The front setback shall be landscaped.

MINOR STREET (Along Canal)	
EDGE	
STREET SECTION R.O.W.: 55' Building Height: Max: 2 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line --- Property Line Hatched Area: Habitable Space Cross-hatched Area: Accessory Building/Dwelling or Parking Area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	40 Percent Minimum at build-to line.
PARKING	All on-site parking shall be accessed from the service road. On-street parking shall count towards the minimum required parking except for single family attached and detached residential uses.
LANDSCAPE/ OPEN SPACE	Landscape shall meet all requirements of Chapter 18-A of this Code and this Article. Street trees shall be planted in a 7' minimum continuous landscape strip.
SETBACK	The front setback shall be 10' or 15' in order to implement urban design principles. The side and rear setbacks shall be as shown above.
OTHER ELEMENTS	Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements. The front setback shall be landscaped.

MINOR STREET (Optional: with no parking)	
CORE	
STREET SECTION R.O.W.: 50' Building Height: Min: 3 stories Max: 6 stories Market District: Max: 2 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line - - - Property Line ▨ Required Colonnade ▨ Habitable Space ▨ Parking and/or allowable building area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	100 Percent Minimum at build-to line.
PARKING	All on-site parking shall be accessed from the service road or minor street. On-street parking shall count towards the minimum required parking. Up to 60% of required parking may be provided off site within a 500' radius.
LANDSCAPE/ OPEN SPACE	Parking lot buffers and street trees shall meet all requirements of Chapter 18-A and this Article except street trees shall have a minimum diameter breast height of 4". Permanent irrigation is required. Street trees shall be planted in 5' x 5' tree grates.
SETBACK	The front front, side, and rear setbacks shall be as shown above.
OTHER ELEMENTS	Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements.

MINOR STREET (Optional: with no parking) CENTER	
STREET SECTION R.O.W.: 50' Building Height: Min: 2 stories Max: 4 stories Market District: Max: 2 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line --- Property Line Hatched Area: Habitable Space Cross-hatched Area: Accessory Building/Dwelling or Parking Area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	75 percent minimum at build-to line. For single family attached only, 100 percent at build-to line.
PARKING	All on-site parking shall be accessed from the service road. On-street parking shall count towards the minimum required parking except for single family attached and detached residential uses.
LANDSCAPE/ OPEN SPACE	Parking lot buffers and street trees shall meet all requirements of Chapter 18-A of this Code and this Article except street trees shall have a minimum diameter breast height of 4". Permanent irrigation is required. Street trees shall be planted in a 5' minimum continuous landscape strip.
SETBACK	The front setback shall be 0' or 10' in order to implement urban design principles. The side and rear setbacks shall be as shown above.
OTHER ELEMENTS	Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements. The front setback shall be landscaped.


MINOR STREET (Optional: with no parking)	
EDGE	
STREET SECTION R.O.W.: 50' Building Height: Max: 2 stories KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line --- Property Line Hatched Area: Habitable Space Cross-hatched Area: Accessory Building/Dwelling or Parking Area	
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	40 Percent Minimum at build-to line.
PARKING	All on-site parking shall be accessed from the service road where provided. On-street parking shall count towards the minimum required parking except for single family attached and detached residential uses.
LANDSCAPE/ OPEN SPACE	Landscape shall meet all requirements of Chapter 18-A of this Code and this Article. Street trees shall be planted in a 7' minimum continuous landscape strip.
SETBACK	The front setback shall be 10' or 15' in order to implement urban design principles. The side and rear setbacks shall be as shown above.
OTHER ELEMENTS	Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements. The front setback shall be landscaped.


SERVICE ROAD	
CORE	
STREET SECTION R.O.W.: 24'	
KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line --- Property Line Hatched Area: Habitable Space Cross-hatched Area: Accessory Building/Dwelling or Parking Area	
LAND USES	Multi-story garages, parking courts, and surface parking. These uses are permitted along service roads only.
BUILDING FRONTAGE	N/A
PARKING	All on-site parking shall be accessed from the service road.
LANDSCAPE/ OPEN SPACE	N/A
SETBACK	N/A
OTHER ELEMENTS	Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements.

SERVICE ROAD	
CENTER	
STREET SECTION R.O.W.: 24'	
KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
LAND USES	Multi-story garages, parking courts, surface parking, single family garages, accessory dwellings, and accessory buildings. These uses are permitted along service roads only.
BUILDING FRONTAGE	N/A
PARKING	All on-site parking shall be accessed from the service road.
LANDSCAPE/ OPEN SPACE	N/A
SETBACK	N/A
OTHER ELEMENTS	Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements.

SERVICE ROAD	
EDGE	
STREET SECTION R.O.W.: 24'	
KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT Key: — Build to Line - - - Property Line Hatched Area: Habitable Space Cross-hatched Area: Accessory Building/Dwelling or Parking Area	
LAND USES	Single family garages, accessory dwellings, and accessory buildings. These uses are permitted along service roads only.
BUILDING FRONTAGE	N/A
PARKING	Service roads are optional in the Edge Sub-district for detached single family only.
LANDSCAPE/ OPEN SPACE	Landscape shall meet all requirements of Chapter 18-A of this Code and this Article. A 6' landscaped strip is required on both sides of paved area.
SETBACK	N/A
OTHER ELEMENTS	Perimeter walls, fences, hedges, entrances and pedestrian pass throughs shall be provided as specified in the General Requirements.

50

PEDESTRIAN PASSAGE	
CORE/CENTER	
STREET SECTION R.O.W.: 15' KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT	N/A
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	50 Percent Minimum for mixed-use buildings only
PARKING	N/A
LANDSCAPE/ OPEN SPACE	Landscape shall meet all requirements of Chapter 18-A of this Code and this Article. Trees are optional and shall be planted in a 5' x 5' minimum tree grate or individual planter.
SETBACK	The setback along the passage shall be 0'.
OTHER ELEMENTS	The hard surfaced area shall be 15' and enhanced with a material different from the sidewalk. The pedestrian passages are optional and shall be interconnected with the sidewalks and public open spaces and provide pedestrian access to parking areas, through blocks, from street to street.

PEDESTRIAN PASSAGE	
EDGE	
STREET SECTION R.O.W.: 15' KEY: s: sidewalk g: green c: curb and gutter ln: lane med: median p: parking bl: bike lane col: colonnade PL: property line Min: Minimum Max: Maximum Req: Required Ded: Dedication	
BUILDING PLACEMENT	N/A
LAND USES	For permitted uses please refer to Sec. 33.284.68 and Sec 33.284.69.
BUILDING FRONTAGE	N/A
PARKING	N/A
LANDSCAPE/ OPEN SPACE	Landscape shall meet all requirements of Chapter 18-A of this Code and this Article. Trees shall be planted in a 4' minimum continuous landscape strip in a random pattern.
SETBACK	The setback along the passage shall be 10' or 15' in order to implement urban design principles.
OTHER ELEMENTS	The hard surfaced area shall be a maximum of 7' and enhanced with a material different from the sidewalk. The pedestrian passages are optional and shall be interconnected with the sidewalks and public open spaces and provide pedestrian access through blocks from street to street.

Section 6. Sec. 33-284.71 of the Code of Miami-Dade County, Florida, is hereby created as follows:

Sec. 33-284.71. General Requirements.

Setbacks, building frontage and building placement shall be as set forth in the Street Types Development Parameters except as specifically provided herein.

A. Lots and blocks.

The following shall be required:

<u>Minimum Lot Requirements</u>			
		<u>Size</u> <u>(Square Feet)</u>	<u>Frontage</u> <u>(Feet)</u>
<u>1.</u>	<u>Single-family attached</u>	<u>2,000</u>	<u>20</u>
<u>2.</u>	<u>Single-family detached and duplex</u>	<u>5,000</u>	<u>50</u>
<u>3.</u>	<u>Live-work units</u>	<u>1700</u>	<u>20 (max 40)</u>
<u>4.</u>	<u>Irregularly shaped lots</u>		<u>15 (*)</u>
<u>5.</u>	<u>All lots shall share a frontage line with a street or an open space</u>		
<u>(*) such lots shall be located only at the end of a series of lots.</u>			
<u>Maximum Block Requirements</u>			
		<u>Length</u> <u>(Feet)</u>	
<u>6.</u>	<u>Maximum length (**)</u>	<u>500</u>	
<u>(**) unless otherwise provided in the Regulating Plans.</u>			

B. Buildings.

1. Storefronts shall be provided on the first floor of mixed-use buildings, directly accessible from a street frontage or an open space as follows:

a. For properties with two or more frontages, storefronts shall be located on a minimum of two frontages with priority given to frontages on an open space and the highest ranking street; and

b. Storefronts shall have a transparent clear glazed area of not less than 70 percent of the facade area. The first floor shall be occupied by habitable uses that generate pedestrian activity and provide a view of the street. Ground floor windowsills shall be placed at a minimum height of 24 inches and a maximum of 48 inches above

- grade. Security enclosures, if any, shall be of the mesh type that pedestrians can see through, and shall be located behind storefront displays.
2. Where colonnades are provided, the finished floor elevation of the colonnade shall match the adjoining sidewalk.
 3. Building streetwall surfaces shall have a minimum of 30 percent of all first floor facades fenestrated with windows. Mirror type glass shall not be allowed. All glazing shall be of a type that permits a view of human activities and spaces within. Colonnade column spacing, windows, and doors shall have a vertical proportion in order that the height dimension is greater than the width dimension of each opening. At least 50 percent of the area of security screens and gates shall be transparent.
 4. In the Core and Center sub-districts in areas where mixed-use is permitted, the build-to line shall be maintained in accordance with the street type development parameters but the building may be set back to accommodate a forecourt. In such circumstance, the building shall be set back no more than 25 feet.
 5. The height of an accessory building shall not exceed the height of the principal building.
 6. An open, covered or paved connection between a principal building and an accessory building may be built within the minimum required 10 feet spacing as shown in the Street Types Development Parameters.
 7. In the Center and Edge sub-districts, awnings, balconies, stoops, stairs, open porches, and bay windows shall be permitted to extend into the minimum front setback, to a maximum of:

	<u>In a setback of 10 feet</u>	<u>In a setback of 15 feet</u>
<u>Bay windows</u>	<u>3 feet</u>	<u>3 feet</u>
<u>Balconies</u>	<u>6 feet</u>	<u>6 feet</u>
<u>Awnings</u>	<u>6 feet</u>	<u>6 feet</u>
<u>Stoops</u>	<u>6 feet</u>	<u>6 feet</u>
<u>Stairs</u>	<u>6 feet</u>	<u>8 feet</u>
<u>Porches</u>	<u>6 to 8 feet</u>	<u>6 to 12 feet</u>

Roof eaves, chimneys, signs, and ramps may encroach into all setbacks. Porticoes, canopies, and colonnades shall be guttered and drainage shall be deposited onsite. In the Center sub-district, awnings may encroach into the right-of way a maximum of 4 feet beyond the property line and signs may encroach a maximum of 2 feet beyond the property line. There shall be a minimum clear height of 8 feet above the sidewalk.

8. In the Core sub-district, bay windows and balconies may encroach beyond the property line a maximum of 3 feet. In the Core sub-district, awnings may encroach into the rights-of-way but shall not extend a distance closer to the street than 6 inches from the face of the curb. All right-of-way encroachments shall be a minimum 8 feet above the sidewalk. Encroachments shall not be taller than the building.
9. In the Edge sub-district, accessory buildings are allowed to have balconies or bay windows that encroach a maximum of 3 feet into the rear yard setback.
10. A cornice line is required on all building facades on U.S. 1 and the Main Street frontages as follows: at the top of the first story of buildings in the Mixed-Use Main Street (MM) area and the top of the second story of buildings in the Mixed-Use U.S.1 (M1) area.
11. Service areas shall be screened and so located as not to be visible at eye-level from adjacent properties or from the street.
12. The primary entrance of a building shall provide access to a public right-of-way or an open space. The primary entrance to the upper levels of mixed-use building with colonnades shall be through the colonnaded area along the front property line.
13. Free-standing colonnades shall not satisfy the build-to line requirement.
14. Colonnades are required along all building frontages facing U.S. 1 and Main Street in the Core sub-district.
15. Each story shall be a maximum of 16 feet clear from floor to ceiling. Each 16-foot portion of a floor in excess of 16 feet, as measured from floor to ceiling, will count as an additional floor, except that one floor may exceed 16 feet, as measured from floor to ceiling, up to 30 feet, provided no mezzanine area exceeds 10 percent of the floor area of that floor.
16. In the Edge sub-district, rowhouses may have up to 3 stories when fronting a green.
17. A live-work unit shall have two components: a workshop and a residential unit. The workshop shall be located on the first floor and shall be directly accessible from the primary street frontage or an open space. The workshop's facade shall have a transparent clear glazed area of not less than 70 percent. The primary entrance of the residential component of a live-unit shall be separate from the workshop component of the unit and shall directly lead to a primary street frontage or an open space

C. Open Space.

Open spaces under this article are classified as (1) designated or (2) private open spaces.

1. Designated open spaces:

- a. The general location, area, and dimensions of designated open spaces shall conform with the Designated Open Space Plan.
- b. Designated open spaces shall (1) include the anchor point depicted on the Regulating Plan, and (2) be provided at grade level.
- c. Provided that all other parameters on the Designated Open Space Plan are met and that the entire designated open space area and an adjacent area are under one ownership, the final location of the designated open space may be pivoted around its anchor point onto the adjacent area, allowing the area previously designated as open space to be developed as permitted in the land use regulating plan.
- d. Designated open spaces shall be provided in the form of squares, greens, or plazas as provided in the Designated Open Space Plan. Lakes, golf courses, and parking lot buffers shall not count towards the open space requirement.
- e. No replatting or other land subdivision shall divide property in such a way that required designated open space is avoided or its location changed.
- f. Designated open spaces shall be shaded and their ground surface shall be a combination of paving materials, lawn or ground cover.
- g. If a lot or group of lots is designated entirely as open space in the Designated Open Space Plan, and is surrounded predominantly by residential parcels, half of the lot or group of lots shall be developable in a contiguous pattern at a density equal to the highest permitted density of any parcel surrounding the lot or group of lots. To achieve such density/intensity, up to two additional floors above the number of floors permitted in the sub-district and Building Heights Plans shall be allowed. Under this circumstance, the developable portion shall not be required to comply with the private open space requirement for residential development provided herein.
- h. If part of a lot or group of lots is designated as open space in the Designated Open Space Plan, the portion not designated as open space shall be developable in a contiguous pattern at a density/intensity which will equal the permitted density/intensity of the entire parcel based upon the density/intensity of the portion of the parcel not designated as open space. To achieve such density, an additional floor above the number of floors permitted in the Street Types Development Parameters shall be allowed.
- i. Around designated open spaces, a building's frontage, height and placement shall be in accordance with the Street Types Development Parameters for the adjacent street.

2. Private open spaces:

56

- a. Private open spaces shall be provided in the form of colonnades, courtyards, terraces, and lawns. Lakes, golf courses, and parking lot buffers shall not count towards the open space requirement.
- b. All residential developments, except for multi-family residential and the live-work units, shall provide a minimum of 400 square feet of private open space per lot, in the form of courtyards, terraces, and lawns.
- c. All multi-family residential developments, including mixed-use developments, shall reserve a minimum of 10 percent of the site for common, private open space. Colonnades, where required, shall count towards this common, private open space requirement.
- d. Private open spaces shall be shaded and their ground surface shall be a combination of paving materials, lawn or ground cover. Enclosures of private open spaces shall be in compliance with paragraph (H) below.
- e. Properties in the Industrial District (ID) area shall provide a minimum of 10 percent of the net lot area as private open space.

D. Landscape.

Landscape shall meet all the requirements of Chapter 18-A of this code except that in the Core and Center sub-districts the following shall apply:

1. Street trees shall be planted at a maximum of 25 feet average on center, with a minimum four-inch diameter at breast height.
2. Street trees are not required when colonnades are being provided along the street.

E. Parking.

Parking shall be provided as required by section 33-124 of this code, except as follows:

1. Multi-story parking garages, parking lots and on-street parking shall count toward all parking requirements except in single family detached residential areas.
2. Parking requirements are as follows:

a.	<u>Single Family Residential (off-street):</u>
(1)	<u>single family detached: 2 spaces/unit</u>
(2)	<u>rowhouse: 2 spaces/unit</u>
(3)	<u>duplex: 2 spaces/unit</u>
b.	<u>Multi-family Residential:</u>
(1)	<u>1.5 spaces/1 bedroom unit</u>
(2)	<u>1.75 spaces/2 bedroom unit</u>
(3)	<u>2 spaces/3 or more bedroom units</u>
c.	<u>Hotel: 1 space/2 guest rooms</u>
d.	<u>Retail: 1 space/250 square feet of building area</u>
e.	<u>Office: 1 space/400 square feet</u>
f.	<u>Restaurants: 1 space/ 50 square feet of patron area</u>
g.	<u>Live-work units:</u> (1) <u>residential component: 2 spaces/unit</u> (2) <u>workshop component: 1 space/325 square feet of workshop area</u>
h.	<u>All other uses shall comply with the parking standards provided in section 33-124 of this code.</u>

3. The combined parking requirement for mixed-use development shall be 90 percent of the total parking otherwise required in this section; provided, however, that in the Core sub-district, the combined parking required for mixed-use development shall be 80 percent of the total parking otherwise required in this section.
4. Mixed-use developments in the Core and Center sub-districts may provide up to 60 percent of the required parking off-site, where the off-site parking is located on a minor street and within 500 feet of the development. Any certificate of use for Mixed-use shall immediately terminate in the event such parking area is not available. An applicant for approval of a Mixed-use development with off-site parking shall execute and record in the public records of this County a declaration of restrictions approved by the Director covenanting that such Mixed-use shall cease and terminate upon the elimination of such parking area, and that no Mixed-use requiring such parking shall be made of such property until the required parking area is available and provided.
5. Residential uses on a lot or group of lots entirely or partially designated as open space located in the Residential Modified (RM) and developed in accordance with paragraph C above, may provide off-site parking for up to 60 percent of the required parking. This off-site parking shall be located on a minor street and within 500 feet of the development. Such residential uses shall immediately terminate in the event such

parking area is not available. An applicant for approval of a RM development with off-site parking shall execute and record in the public records of this County a declaration of restrictions approved by the Director covenanting that such residential use shall cease and terminate upon the elimination of such parking area, and that no residential use requiring such parking shall be made of such property until the required parking area is available and provided.

6. Parking for individuals with disabilities and persons transporting strollers shall be provided in compliance with section 33-122 of this code.

7. Except for detached single-family homes and duplexes, all parking may be in the form of multi-story parking garage structures or parking lots that are located in the rear or on one side of the building and are screened from public right-of-way. Parking is not permitted in the front setback.

8. At a minimum, the first floor of Multi-story parking garage structures shall be screened along all frontages, except along a service road, by a liner building containing habitable space at a minimum depth of 20 feet. Surface parking lots shall be located to the rear of buildings. Parking lots shall be screened along all frontages, except rear.

9. In the Center sub-district, driveways shall be allowed only from service roads. In the Core sub-district, driveways shall be allowed only from service roads or minor streets.

10. Parking for detached single family homes and duplexes in the Edge sub-district shall be subject to the following:

a. Where there is no service road, parking shall be in the form of individual garages or carports accessed through a driveway from the street. Along the front property line the maximum width of the driveways in front of the build-to line shall be 10 feet. On any other frontage the maximum width of the driveway shall be 20 feet.

b. The parking area shall be screened at the build-to line through the use of walls, hedges or fences.

c. Attached garages and carports shall be placed a minimum of 20 feet behind the build-to-line and shall be setback a minimum of 5 feet from the nearest side property line and detached garages shall be placed as provided in the Street Types Development Parameters.

d. The sidewalk shall be continuous and remain at a constant level at all instances where a driveway intersects it.

F. Streets, service roads and utilities.

All streets shall be located according to the New Streets Plan and the Street Type Development Parameters. All new A streets shall be in the same general location shown on the New Streets Plan and may be modified with respect to alignment provided that the final alignment is in keeping with the principles of good urban design. All new B streets shall be in the same general location as shown on the New Streets Plan and may be modified only with respect to alignment and orientation provided that the final alignment and orientation are in keeping with the principles of good urban design and the criteria listed below. All streets shall allow general public access. Privately owned streets shall be subject to an approved plat restriction to allow general public access. No gates that impede through traffic are permitted along A or B streets. No new A and B streets shall be deleted. B streets may be modified by the Director so long as the following requirements are met:

- a. The modification shall be approved by the Director and the Director of Public Works who shall review the proposed modification for traffic and safety issues.
- b. The modification shall not diminish the general size and location of an open space shown in the Designated Open Space Plan.
- c. The street modification shall maintain connectivity to the surrounding area.
- d. The modification shall allow for the appropriate use of private property.

The design of new streets and modifications of existing streets shall also comply with the following requirements:

1. Street rights-of-way shall be in accordance with the Street Type Development Parameters.
2. All streets and service roads shall connect to other streets or service roads. Cul-de-sacs, T-turnarounds, and dead end streets are not permitted.
3. All sidewalks are required to comply with the following:

Sidewalks		
a.	Minimum width	6 feet (*)

b.	<u>Minimum unobstructed area</u>	<u>60 inches</u>
c.	<u>Where a colonnade is required outside the right-of-way, free and clear use of sidewalk area shall be maintained and a continuous unobstructed area of 60 inches from the property line into the property shall be kept clear.</u>	
d.	<u>All sidewalks shall be unobstructed by utilities poles, fire hydrants or any other temporary or permanent structures.</u>	
<u>(*) unless a different width is required by the Street Development Parameters</u>		

4. Where on-street parking is provided, parking lanes shall be no closer than 25 feet from the intersection measured from the outermost point of the nearest corner property line.

5. At intersections the following requirements apply:

	<u>Sub-district</u>	<u>Type of Streets</u>	<u>Required Curb Radii and Clear Zone Radius</u>
a.	<u>Core sub-district</u>	<u>All streets</u>	<u>20' curb radii</u> <u>25' clear zone</u>
b.	<u>Center sub-district</u>	<u>Main Street</u>	<u>20' curb radii</u> <u>25' clear zone</u>
c.	<u>Center sub-district</u>	<u>Minor Street and Boulevard</u>	<u>15' curb radii</u> <u>25' clear zone</u>
d.	<u>Edge sub-district</u>	<u>All streets</u>	<u>15' curb radii</u> <u>25' clear zone</u>

6. Curb and gutters are required at:

	<u>Sub-district</u>	
a.	<u>All</u>	<u>All intersections at roadway edges of US 1, Boulevards and Main Street.</u>
b.	<u>Core and Center</u>	<u>At all intersections and at roadway edges of minor streets.</u>

7. With the exception of fire hydrants, utilities shall run underground.

G. Street Lighting.

The following shall be required:

<u>1.</u>	<u>Street lighting shall be provided in these areas: commercial and live-work units driveways and parking areas, sidewalks and pedestrian passages, commercial establishments entryways, recreation areas, and multi-family residential common areas and entryways.</u>
<u>2.</u>	<u>Outdoor lighting of these areas shall be in compliance with section 33-4.1 of this code.</u>
<u>3.</u>	<u>All light fixtures shall be of a pedestrian scale with:</u> <u>Max. Height: 18'</u> <u>Max. Spacing: 40'</u>
<u>4.</u>	<u>The type and spacing of light fixtures shall be approved by the Department of Public Works. Approval shall be based on uniformity of types, location, right-of-way width and luminosity.</u>
<u>5.</u>	<u>Weather and vandalism resistant covers shall protect all light fixtures.</u>
<u>6.</u>	<u>Streetlamps shall be installed on both sides of streets.</u>
<u>7.</u>	<u>Cobra-head lights shall not be permitted.</u>

H. Walls, fences, and hedges.

The following shall be permitted:

Location	Type and Material	Posts and Pillars	Height	Transparency/Opacity
Around perimeter of designated open space	Walls and Fences: Masonry, wood, electrostatic plated aluminum, or wrought iron	Max. 10' Apart	Max. 3'-6"	75% Minimum Transparent
	Hedges and shrubs	Max. 30" O.C.	At time of planting Min. 18"	N/A
		Max. 48" O.C.	Max. 3'-6"	
In front of the build-to-line (BL), Along front (F), corner side (CS), interior side (IS), and rear (R) property lines	Walls and Fences: Masonry, wood, electrostatic plated aluminum, or wrought iron	Max. 10' Apart	Max. 3'-6"	75% Minimum Transparent
	Hedges and shrubs	Max. 30" O.C.	At time of planting Min. 18"	N/A
		Max. 48" O.C.	Max. 3'-6"	
Behind the build-to-line (BL), Along interior side (IS) and rear (R) property lines	Walls and Fences: Masonry, wood, electrostatic plated aluminum, or wrought iron	N/A	Min. 60" Max. 72"	75% Minimum Opaque
	Hedges and shrubs	Max. 30" O.C.	At time of planting Min. 18"	N/A
		Max. 48" O.C.	Max. 72"	
	Chain Link	N/A	Min. 60" Max. 72"	N/A

<u>Location</u>	<u>Type and Material</u>	<u>Posts and Pillars</u>	<u>Height</u>	<u>Transparency/Opacity</u>
<u>Along the build-to-line (BL)</u>	<u>Walls and Fences: Masonry, wood, electrostatic plated aluminum, or wrought iron</u>	<u>Max. 10' Apart</u>	<u>Min. 48"</u> <u>Max. 72"</u>	<u>75% Minimum Opaque</u>
	<u>Hedges and shrubs</u>	<u>Max. 30" O.C.</u>	<u>At time of planting Min. 18"</u>	<u>N/A</u>
		<u>Max. 48" O.C.</u>	<u>Max. 72"</u>	
<u>Parking Areas Along Streets</u>	<u>Walls and Fences: Masonry, wood, electrostatic plated aluminum, or wrought iron</u>	<u>Max. 10' Apart</u>	<u>Min. 3'-6"</u>	<u>75% Minimum Opaque</u>
	<u>Hedges and shrubs</u>	<u>Max. 48" O.C.</u>	<u>At time of planting Min. 3'-6"</u>	<u>N/A</u>
		<u>N/A</u>	<u>N/A</u>	<u>N/A</u>
<u>Construction Areas</u> <u>Industrial Areas Along B Streets Only</u>	<u>Chain Link</u>	<u>N/A</u>	<u>N/A</u>	<u>N/A</u>
	<u>Chain Link</u>	<u>N/A</u>	<u>N/A</u>	<u>N/A</u>

Note:

1. Hedges and shrubs shall be subject to Chapter 18-A of this code.
2. Where a wall or fence is used for screening parking areas along streets a 5-foot landscape strip shall be required in front of the wall or fence.
3. The maximum spacing for pillars and posts shall apply except along driveways.

I. Outdoor uses/enclosed uses.

All uses shall be conducted within completely enclosed buildings, except outdoor uses expressly permitted in this article, and except that materials and products may be stored within an area completely enclosed within walls having a life expectancy of 20 years or more from the date of installation and of sufficient height to screen such materials and products from view at eye level. Storage shall not be visible above the height of the walls. Commercial trucks shall be stored or parked within an enclosed building or an area enclosed by a fence, wall, or hedge in a manner that precludes visibility at the eye-level from adjacent properties.

Section 7. Sec. 33-284.72 of the Code of Miami-Dade County, Florida, is hereby created as follows:

Sec. 33-284.72. Signs.

Except as expressly provided herein, signage shall comply with section 33-284.63 of this code.

A. Temporary point of sale signs

Temporary point of sales are permitted when in compliance with the following:

<u>1.</u>	<u>Size:</u>	<u>1.5 square feet maximum</u>
<u>2.</u>	<u>Number of signs:</u>	<u>One sign per lot frontage</u>
<u>3.</u>	<u>Setback and spacing:</u>	<u>The outer edge of sign shall be no closer than 5 feet to an official right-of-way line unless attached to an existing building, and shall be no closer than 15 feet to an interior side property line or shall be centered on a lot between interior side property lines.</u>
<u>4.</u>	<u>Illumination/lighting:</u>	<u>Section 33-96 of this code shall apply.</u>
<u>5.</u>	<u>Maximum height:</u>	<u>The maximum height to top of sign shall be 6 feet for detached signs. For attached signs, minimum height shall be 5 feet above grade.</u>
<u>6.</u>	<u>Special conditions</u>	<u>No permit shall be required for signs that are less than 1.5 square feet and that are not electrically illuminated.</u>

B. Permanent Point of Sale Signs.

Permanent point of sale signs are permitted provided that:

<u>1.</u>	<u>The following permanent point of sale signs are permitted in all sub-districts in conjunction with permitted business and industrial uses: detached, flat attached, hanging, awning, and cantilever projecting.</u>			
<u>a.</u>	<u>Cantilever projecting signs shall be mounted and perpendicular to the building.</u>			
<u>b.</u>	<u>The copy of an awning sign shall be located only on the valance of the awning.</u>			
<u>c.</u>	<u>The bottom of a hanging sign shall be located at a minimum height of 8' from the finished floor.</u>			
<u>2.</u>	<u>Size, location and number shall be as follows:</u>			
<u>Sub-districts</u>	<u>Maximum Size</u>	<u>Uses</u>	<u>Street Frontage</u>	<u>Number of Signs</u>
<u>All</u>	<u>6 sq. ft.</u>	<u>Business/Mixed-Use/Live- Work</u>	<u>All Streets</u>	<u>one of each type per street frontage</u>
<u>All</u>	<u>6 sq. ft.</u>	<u>Industrial</u>	<u>A Streets</u>	<u>one of each type per street frontage</u>
<u>All</u>	<u>32 sq. ft.</u>	<u>Industrial</u>	<u>B Streets</u>	<u>one per street frontage</u>
<u>3.</u>	<u>Illumination/lighting:</u>		<u>Section 33-96 of this code shall apply.</u>	
<u>4.</u>	<u>Maximum height:</u>		<u>four feet maximum height above grade to top of sign for detached signs; no limits for flat attached signs. The maximum height of the copy for signs painted on the façade of a building or on the valance of an awning shall be 1 foot.</u>	

C. Prohibited Signs.

The following types of outdoor signs are not permitted: automatic electric changing signs, revolving, rotating, and otherwise moving signs, backlit awnings, backlit neon, banners, flags, roof signs and balloon signs.

Section 8. Sec. 33-284.73 of the Code of Miami-Dade County, Florida, is hereby created as follows:

Sec. 33-284.73. Review Procedure/Administrative Site Plan and Architectural Review.

All new development within the NCUC District, except an individual single family home or duplex home, shall be consistent with the requirements of this article and with the site plan and architectural review criteria contained herein. Applications for administrative approval shall be processed and approved as follows: The review procedures for developments, except in the case of an individual single-family home and duplexes, shall include (A) a pre-submittal conference and (B) a site and architectural plan review.

A. Pre-submittal conference.

Except when related to the development of an individual single-family home or duplex home, all applicants for site plan approval shall meet with the Department prior to submittal of an application for administrative site and architectural plan review. The concepts of the applicant's proposal shall be evidenced schematically by sketch plans, elevations, and narrative information sufficient for a general understanding of the proposed development. Within 21 days after the pre-submittal conference, the Director shall provide the applicant with all written comments resulting from such conference, including appropriate recommendations to inform and assist the applicant to proceed with the development of the plans for subsequent review.

B. Administrative site plan and architectural plan review.

The Department shall review plans including the exhibits listed below for completeness and compliance with the provisions of this article, including the Regulating Plans, and for compliance with the site plan review criteria provided herein. All complete submissions to the Department shall be reviewed and approved or denied within 21 days after the date of submission. The applicant shall have the right to extend the 21-day period by an additional 21 days upon timely request made in writing to the Department. The Department shall have the right to extend the 21-day period by written notice to the applicant that additional information is needed to process the site plan. Denials shall be in writing and shall specifically set forth the grounds for the denial. Any final decision of

the Director may be appealed in accordance with the procedures established in this Chapter for appeals of administrative decisions.

Applications for administrative site plan and architectural plan review under this article shall be accompanied by exhibits prepared by registered architects and landscape architects which shall be submitted to the Department and shall include the following:

1. Site plan(s) including:
 - a. sub-district location;
 - b. street layouts and designations as per this article;
 - c. locations, shape, size, and height of existing buildings;
 - d. indication of street vistas;
 - e. lot lines, setbacks and build-to-lines;
 - e. location of open spaces including anchor points if applicable;
 - g. location of on-street and off-street parking, loading facilities, and waste collection areas;
 - h. indication of signage; and
 - i. indication of any site or building design methods used to conserve energy.
2. Landscape plans including specifications of species of plant material, location, and size in accordance with this article and Chapter 18A of this code.
3. Street cross sections including adjacent buildings and open space.
4. Floor plans, elevations and sections of all buildings, including total gross square feet of area for each floor and all dimensions relating to the requirements of this article. A pattern book may be submitted for detached and attached single-family units including, at a minimum, unit plans and elevations, elevation of unit groupings, and typical design details such as street lamps, benches, fencing, and paving details.
5. Figures indicating the following:
 - a. gross and net acreage;
 - b. total square footage for each of the use by types;
 - c. total number of dwelling units;
 - d. amount of passive and active open space in square feet; and
 - e. such other design data as may be needed to evaluate the project's compliance with the requirements of this article and Chapter.

Section 9. Sec. 33-284.74 of the Code of Miami-Dade County, Florida, is hereby created as follows:

Sec. 33-284.74. Zoning relief from certain requirements.

Relief from the following requirements of this article shall be permitted only pursuant to the standards and requirements of section 33-311(A)(4)(a) of this code:

1. minimum and maximum densities;
2. required liner buildings used to screen parking;
3. colonnade requirements, including minimum horizontal and vertical clearances;
4. location and provision of A streets and B Streets;
5. requirements for street trees, greens, plazas, squares and medians;
7. maximum size of blocks;
8. curb requirement in the Core and Center sub-district; and
9. signage.

Section 10. Sec. 33-284.75 of the Code of Miami-Dade County, Florida, is hereby created as follows:

Sec. 33-284.75. Conflicts with other chapters and regulations.

This article shall govern in the event of conflicts between this article and other zoning, subdivision, or landscape regulations of this code.

Section 11. Sec. 33-284.76 of the Code of Miami-Dade County, Florida, is hereby created as follows:

Section 33-284.76. Non-conforming Structures, Uses, and Occupancies.

Nothing contained in this article shall be deemed or construed to prohibit a continuation of a legal nonconforming structure, use, and occupancy in the NCUC District that either (1) was existing as of the effective date of this ordinance (_____, 2004) or (2) on or before said date, had received final site plan approval through a public hearing pursuant

to this chapter or through administrative site plan review. However, any structure, use or occupancy in the NCUC District that is discontinued for a period of at least six months, or is superseded by a lawful structure, use or occupancy permitted under this chapter, or that incurs damage to the roof or structure to an extent of 50 percent or more of its market value, shall be subject to section 33-35(c) of this code.<<

Section 12. Sec. 33-311 of the Code of Miami-Dade County, Florida, is hereby amended as follows:

Sec. 33-311. Community Zoning Appeals Board – Authority and Duties.

- (A) Except as otherwise provided by this chapter, the Community Zoning Appeals Boards and Board of County Commissioners shall have the authority and duty to consider and act upon applications, as hereinafter set forth, after first considering the written recommendations thereon of the Director or Development Impact Committee.

* * *

- (13) Hear applications to modify or eliminate any condition or part thereof which has been imposed by any final decision adopted by resolution regulating any parcel of land located within the Downtown Kendall Urban Center >>or the Naranja Community Urban Center<< zoning district>>s<<, where and to the extent that modification or elimination of the condition or part thereof is necessary to allow development conforming in all respects to the Downtown Kendall Urban Center District, sections 33-284.55--33-284.65 of this code >>or the Naranja Community Urban Center District, sections 33-284.66–33-284.76 of this code<<.

Section 13. Sec. 33-314 of the Code of Miami-Dade County, Florida, is hereby amended to read as follows:

Sec. 33-314. Direct applications and appeals to the County Commission.

* * *

- (B) The County Commission shall have jurisdiction to hear appeals from decision of the Community Zoning Appeals Boards as follows:

* * *

>>(12) Applications for development approval or modifications thereof for projects located within the Center or Edge sub-districts of the Naranja Community Urban Center District.<<

- (C) The County Commission shall have jurisdiction to directly hear other applications as follows:

* * *

>>(11) Applications for development approval or modifications thereof for projects located within the Core sub-district of the Naranja Community Urban Center District after hearing and recommendation by the Community Zoning Appeals Board or Boards having jurisdiction over the area encompassed by the project.<<

Section 14. If any section, subsection, sentence, clause or provision of this ordinance is held invalid, the remainder of this ordinance shall not be affected by such invalidity.

Section 15. It is the intention of this Board of County Commissioners, and is hereby ordained that the provisions of this ordinance shall become and made part of the Code of Miami-Dade County, Florida. The section of this ordinance may be renumbered or relettered to accomplish such intention, and the word "ordinance" may be changed to "section", "article" or other appropriate word.

Section 16. This ordinance shall become effective ten (10) days after the date of enactment unless vetoed by the Mayor, and if vetoed, shall become effective only upon an override by this Board.

PASSED AND ADOPTED:

Approved by County Attorney as
to form and legal sufficiency:

RAZ

Prepared by:

SA

Joni Armstrong Coffey